Produkte
Mainboard Serie
»H67DE3
»Überblick
»Spezifikationen
»Download
»Handbuch
»FAQ
»CP Support Liste
»Speicher Support Liste

Welcome to ASRock COMPUTEX Taipei 2011 May 31st - June 4th L317a, 4F, TWTC Nangang Hall

ASRocks brandneues P67/H67-Motherboard mit B3-Stepping-Chipsatz steht in den Startlöchern

Statement for Intel 6 Series Chipset Issue

ASRock Channel on YouTube

facebook Follow ASRock on facebook now!

ASRock Forum

FATAL1TY

Absolute Performance P67 / H67 / H61 Series

Vision 3D

XFast USB Boosts up your USB speed

SmartView

H67DE3

SHARE |

- 100% All Solid Capacitor design
- Supports Intel® K-series CPU
- Supports Dual Channel DDR3 1333
- Intel® HD Graphics 2000/3000 and new Visual Features, DX10.1, Pixel Shader 4.1
- Supports Blu-ray Stereoscopic 3D with HDMI 1.4a
- Multi VGA Output options: D-Sub, DVI-D and HDMI
- 2 x USB 3.0 ports, 2 x SATA3 connectors
- Supports ASRock Extreme Tuning Utility (AXTU), XFast USB, Graphical UEFI, Instant Boot, Instant Flash, Good Night LED, APP Charger, SmartView
- Combo Cooler Option (C.C.O.)
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec), Premium Blu-ray audio support
- Free Gift : 1 x 3D Red/Cyan Anaglyph Glasses

Dieses Modell wird möglicherweiße nicht weltweit verkauft. Bitte kontaktieren Sie ihren Händler für Informationen über die Verfügbarkeit in ihrerer Region.

Youtube Live Demo

ASRock XFast USB

ASRock H67 3D Video Experience in Taipei Flower Expo

Produkt Spezifikationen

Generelles	
CPU	- Supports 2nd Generation Intel® Core™ i7 / i5 / i3 in LGA1155 Package - Supports Intel® Turbo Boost 2.0 Technology - Supports Intel® K-series CPU - Supports Hyper-Threading Technology
Chipsatz	- Intel® H67
Arbeitsspeicher	- Dual Channel DDR3 memory technology - 4 x DDR3 DIMM slots - Supports DDR3 1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 32GB* *Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 64Mb AMI UEFI Legal BIOS with GUI support - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - IGPU, DRAM, PCH, CPU PLL, VTT, VCCSA Voltage Multi-adjustment
Audio, Video und Netzwerk	
Grafik	- Supports Intel® HD Graphics Built-in Visuals : Intel® Quick Sync Video, Intel® InTru™ 3D, Intel® Clear Video HD Technology, Intel® HD Graphics 2000/3000, Intel® Advanced Vector Extensions (AVX) - Pixel Shader 4.1, DirectX 10.1 - Max. shared memory 1759MB - Multi VGA Output options: D-Sub, DVI-D and HDMI - Supports HDMI 1.4a Technology with max. resolution up to 1920x1200 @ 60Hz - Supports DVI with max. resolution up to 1920x1200 @ 60Hz - Supports D-Sub with max. resolution up to 2048x1536 @ 75Hz - Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI (Compliant HDMI monitor is required) - Supports Blu-ray Stereoscopic 3D with HDMI 1.4a - Supports HDCP function with DVI and HDMI ports - Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI and HDMI ports *Due to chipset limitation, the Blu-ray playback of Intel® HD Graphics is only supported under Windows® Vista™ and Windows® 7. **Intel® InTru™ 3D is only supported under Windows® 7 and Windows® 7 x64.
Audio	- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec) - Premium Blu-ray audio support
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtek RTL8111E - Supports Wake-On-LAN - Supports LAN Cable Detection - Supports Energy Efficient Ethernet 802.3az - Supports PXE
Erweiterungsslots/Konnektivität	

Steckplätze	- 1 x PCI Express 2.0 x16 slot (blue @ x16 mode) - 3 x PCI Express 2.0 x1 slots - 2 x PCI slots
SATA3	- 2 x SATA3 6.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10, RAID 5 and Intel® Rapid Storage), NCQ, AHCI and "Hot Plug" functions
USB 3.0	- 2 x USB 3.0 ports by Etron EJ168A, support USB 1.0/2.0/3.0 up to 5Gb/s
Anschluss	- 4 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10, RAID 5 and Intel® Rapid Storage), NCQ, AHCI and Hot Plug functions - 2 x SATA3 6.0 Gb/s connectors - 1 x IR header - 1 x CIR header - 1 x COM port header - 1 x HDMI_SPDIF header - 1 x Power LED header - CPU/Chassis/Power FAN connector - 24 pin ATX power connector - 8 pin 12V power connector - Front panel audio connector - 2 x USB 2.0 headers (support 4 USB 2.0 ports) *Please noted that AHCI/RAID mode is not supported under Windows® XP/XP 64bit OS.
ATX-Blende	I/O Panel - 1 x PS/2 Keyboard Port - 1 x VGA/D-Sub Port - 1 x VGA/DVI-D Port - 1 x HDMI Port - 1 x Optical SPDIF Out Port - 4 x Ready-to-Use USB 2.0 Ports - 2 x Ready-to-Use USB 3.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	

Einzigartige Features	- ASRock Extreme Tuning Utility (AXTU)
	- Instant Boot
	- ASRock Instant Flash
	- ASRock AIWI
	- ASRock APP Charger
	- SmartView
	- Hybrid Booster:
	  - ASRock U-COP
	  - Boot Failure Guard (B.F.G.)
	- Combo Cooler Option (C.C.O.)
	- Good Night LED

Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), ASRock Software Suite (CyberLink DVD Suite - OEM and Trial; Creative Sound Blaster X-Fi MB - Trial)
Produktzubehör	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA Data Cables (optional) - 1 x 3D Red/Cyan Anaglyph Glasses (optional)
Hardware überwachung	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU/Chassis/Power Fan Tachometer - CPU/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU or MB Temperature) - CPU/Chassis Fan Multi-Speed Control - Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore
Formfaktor	- ATX Form Factor: 12.0-in x 8.3-in, 30.5 cm x 21.1 cm - All Solid Capacitor design
Betriebssystem	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant
Zertifizierungen	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko bürgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursachet werden sind wir nicht verantwortlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.

© 2002-2011 ASRock Inc Alle Rechte vorbehalten | Informationen die auf asrock.com veröffentlicht werden, können ohne Hinweis geändert werden.